



CARGO CONTROL

PHONE (920) 851-5845 • FAX (920) 734-7615 • APPLETON, WI 54911

10 STANDARD SLING TYPES

LET YOU SELECT THE BEST SLING FOR EVERY LIFT . . .

TYPE 1



**TRIANGLE
CHOKER**

Slip-through triangle provides smooth, even choke for single-leg lifts.

Width to 12"

TYPE 2



**TRIANGLE-
TRIANGLE**

Choice of several permanently attached fittings of steel or aluminum alloy offers a greater variety of attachments or hitch configurations.

Width to 12"

TYPE 3



**EYE & EYE
FLAT**

Eye is formed by folding back the webbing and sewing it flat against the sling body.

Width to 12"

TYPE 4




**EYE & EYE
TWIST**

Fabric is turned 180° before sewing to form an eye which lays 90° to the sling body. This allows for easier choking.

Width to 12"

TYPE 5



**ENDLESS OR
GROMMET**

Fabric is overlapped and sewn to form an endless grommet; areas of hook contact may be tapered and reinforced for longer wear.

Width to 12"

TYPE 6



**REVERSED
EYE**

Eye is formed by folding back the webbing and sewing it side by side.

Width to 12"

TYPE 7



**FLAT
EYE**

Fabric is turned 180° to form an eye which lays on the same plane as the sling body.

Width to 12"

TYPE 8



**WIDE BODY
BASKET**

Wide body slings provide greater stability in basket hitches. Eyes are folded and sewn to form hook openings.

Width to 48"

TYPE 9



**LOAD
BALANCER
BASKET**

A light-duty basket for use where load balancing or cradling is required.

Width to 48"

TYPE 10



**MULTI-LEG
BRIDLES**

Bridles offer a variety of leg designs for quick hook-up on repetitive lifts. Three or more legs available on special request.